R-454C

A-Gas (New Zealand) Limited

Chemwatch Hazard Alert Code: **4**

Chemwatch: **5296-59**
Version No: **7.1**
Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Initial Date: **26/03/2018**
Revision Date: **01/05/2026**
Print Date: **02/11/2026**
L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	R-454C
Synonyms	Not Available
Proper shipping name	LIQUEFIED GAS, FLAMMABLE, N.O.S. (contains difluoromethane and 2,3,3,3-tetrafluoropropene)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Refrigerant For professional and industrial installation and use only. Do not use product for anything outside of the above specified uses. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Details of the manufacturer or importer of the safety data sheet

Registered company name	**A-Gas (New Zealand) Limited**
Address	68 Rangi Road Takanini 2105 New Zealand
Telephone	+64 0800 992 427
Fax	Not Available
Website	www.agas.com
Email	Not Available

Emergency telephone number

Association / Organisation	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone number(s)	**+64 800 700 112 (ID#: 5296-59)**
Other emergency telephone number(s)	**+61 3 9573 3188**

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Flammable gases, Hazard Category 1A, Gases Under Pressure (Liquefied Gas)
Legend:	*1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI*
Determined by Chemwatch using GHS/HSNO criteria	2.1.1A

Label elements

Page 1 continued...

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautionary statement(s) Response

P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	In case of leakage, eliminate all ignition sources.

Precautionary statement(s) Storage

P410+P403	Protect from sunlight. Store in a well-ventilated place.

Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
754-12-1	>60	2,3,3,3-tetrafluoropropene
75-10-5	10-30	difluoromethane

Legend:	*1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available*

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	‣ If product comes in contact with eyes remove the patient from gas source or contaminated area. ‣ Take the patient to the nearest eye wash, shower or other source of clean water. ‣ Open the eyelid(s) wide to allow the material to evaporate. ‣ Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners. ‣ The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage. ‣ Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) ‣ Transport to hospital or doctor. ‣ Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur. ‣ If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage. ‣ Ensure verbal communication and physical contact with the patient. **DO NOT** allow the patient to rub the eyes

Continued...

	DO NOT allow the patient to tightly shut the eyes **DO NOT** introduce oil or ointment into the eye(s) without medical advice **DO NOT** use hot or tepid water.
Skin Contact	If skin or hair contact occurs: ‣ Flush skin and hair with running water (and soap if available). ‣ Seek medical attention in event of irritation. In case of cold burns (frost-bite): ‣ Move casualty into warmth before thawing the affected part; if feet are affected carry if possible ‣ Bathe the affected area immediately in luke-warm water (not more than 35 deg C) for 10 to 15 minutes, immersing if possible and without rubbing ‣ **DO NOT** apply hot water or radiant heat. ‣ Apply a clean, dry, light dressing of "fluffed-up" dry gauze bandage ‣ If a limb is involved, raise and support this to reduce swelling ‣ If an adult is involved and where intense pain occurs provide pain killers such as paracetomol ‣ Transport to hospital, or doctor ‣ Subsequent blackening of the exposed tissue indicates potential of necrosis, which may require amputation.
Inhalation	‣ Following exposure to gas, remove the patient from the gas source or contaminated area. ‣ NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. ‣ Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. ‣ If the patient is not breathing spontaneously, administer rescue breathing. ‣ If the patient does not have a pulse, administer CPR. ‣ If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. ‣ Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction. ‣ Keep the patient warm, comfortable and at rest while awaiting medical care. ‣ **MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.** ‣ Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	‣ Not considered a normal route of entry. ‣ For advice, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;
A: Emergency and Supportive Measures
- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours

B: Specific drugs and antidotes:
- There is no specific antidote

C: Decontamination
- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. **DO NOT** induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)

D: Enhanced elimination:
- There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition
- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient

For frost-bite caused by liquefied petroleum gas:
- If part has not thawed, place in warm water bath (41-46 C) for 15-20 minutes, until the skin turns pink or red.
- Analgesia may be necessary while thawing.
- If there has been a massive exposure, the general body temperature must be depressed, and the patient must be immediately rewarmed by whole-body immersion, in a bath at the above temperature.
- Shock may occur during rewarming.
- Administer tetanus toxoid booster after hospitalization.
- Prophylactic antibiotics may be useful.
- The patient may require anticoagulants and oxygen.

[Shell Australia 22/12/87]
For gas exposures:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.

Continued...

- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Extinguishing media

DO NOT EXTINGUISH BURNING GAS UNLESS LEAK CAN BE STOPPED SAFELY:
OTHERWISE: LEAVE GAS TO BURN.

FOR SMALL FIRE:

- Dry chemical, CO2 or water spray to extinguish gas (only if absolutely necessary and safe to do so).
- **DO NOT** use water jets.

FOR LARGE FIRE:

- Cool cylinder by direct flooding quantities of water onto upper surface until well after fire is out.

Special hazards arising from the substance or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	FOR FIRES INVOLVING MANY GAS CYLINDERS: ‣ To stop the flow of gas, specifically trained personnel may inert the atmosphere to reduce oxygen levels thus allowing the capping of leaking container(s). ‣ Reduce the rate of flow and inject an inert gas, if possible, before completely stopping the flow to prevent flashback. ‣ **DO NOT extinguish the fire until the supply is shut off** otherwise an explosive re-ignition may occur. ‣ If the fire is extinguished and the flow of gas continues, used increased ventilation to prevent build-up, of explosive atmosphere. --- GENERAL --- ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Consider evacuation ‣ Fight fire from a safe distance, with adequate cover.
Fire/Explosion Hazard	‣ HIGHLY FLAMMABLE: will be easily ignited by heat, sparks or flames. ‣ Will form explosive mixtures with air ‣ Fire exposed containers may vent contents through pressure relief valves thereby increasing fire intensity and/ or vapour concentration. ‣ Vapours may travel to source of ignition and flash back. ‣ Containers may explode when heated - Ruptured cylinders may rocket ‣ Fire may produce irritating, poisonous or corrosive gases. Combustion products include: ‣ carbon monoxide (CO) ‣ carbon dioxide (CO2) hydrogen fluoride ‣ other pyrolysis products typical of burning organic material. **Contains low boiling substance:** Closed containers may rupture due to pressure buildup under fire conditions. ‣ Vented gas is more dense than air and may collect in pits, basements.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

Continued...

See section 12

Methods and material for containment and cleaning up

Minor Spills	‣ Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. ‣ **DO NOT** enter confined spaces where gas may have accumulated. ‣ Shut off all sources of possible ignition and increase ventilation.
Major Spills	‣ Clear area of all unprotected personnel and move upwind. ‣ Alert Emergency Authority and advise them of the location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear full body clothing with breathing apparatus. ‣ Remove leaking cylinders to a safe place. ‣ Fit vent pipes. Release pressure under safe, controlled conditions ‣ Burn issuing gas at vent pipes. ‣ DO NOT exert excessive pressure on valve; DO NOTattempt to operate damaged valve.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	· Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature · The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines. · Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended. · Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas. ‣ Avoid generation of static electricity. Earth all lines and equipment. ‣ **DO NOT** transfer gas from one cylinder to another.
Other information	‣ Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. ‣ Such compounds should be sited and built in accordance with statutory requirements. ‣ The storage compound should be kept clear and access restricted to authorised personnel only. ‣ Cylinders stored in the open should be protected against rust and extremes of weather.

Conditions for safe storage, including any incompatibilities

Suitable container	‣ **DO NOT** use aluminium or galvanised containers ‣ Cylinder: ‣ Ensure the use of equipment rated for cylinder pressure. ‣ Ensure the use of compatible materials of construction. ‣ Valve protection cap to be in place until cylinder is secured, connected. ‣ Cylinder must be properly secured either in use or in storage.
Storage incompatibility	As a general rule, hydrofluorocarbons tend to be flammable unless they contain more fluorine atoms than hydrogen atoms. Haloalkanes: ‣ are highly reactive:some of the more lightly substituted lower members are highly flammable; the more highly substituted may be used as fire suppressants, not always with the anticipated results. ‣ may react with the lighter divalent metals to produce more reactive compounds analogous to Grignard reagents. ‣ may produce explosive compounds following prolonged contact with metallic or other azides ‣ may react on contact with potassium or its alloys - although apparently stable on contact with a wide rage of halocarbons, reaction products may be shock-sensitive and may explode with great violence on light impact; severity generally increases with the degree of halocarbon substitution and potassium-sodium alloys give extremely sensitive mixtures . BRETHERICK L.: Handbook of Reactive Chemical Hazards ‣ react with metal halides and active metals, eg. sodium (Na), potassium (K), lithium (Li),calcium (Ca), zinc (Zn), powdered aluminium (Al) and aluminium alloys, magnesium (Mg) and magnesium alloys. ‣ Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances



+	x	+	x	+	+	+

X — *Must not be stored together*
0 — *May be stored together with specific preventions*
+ — *May be stored together*

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

Continued...

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

MATERIAL DATA

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Individual protection measures, such as personal protective equipment	
Eye and face protection	‣ Safety glasses with side shields ‣ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] ‣ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	‣ When handling sealed and suitably insulated cylinders wear cloth or leather gloves. ‣ Insulated gloves: ‣ NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upon them. Insulated gloves are not made to permit hands to be placed in the liquid; they provide only short-term protection from accidental contact with the liquid.
Body protection	See Other protection below
Other protection	‣ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton. ‣ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost. BRETHERICK: Handbook of Reactive Chemical Hazards. ‣ Protective overalls, closely fitted at neck and wrist. ‣ Eye-wash unit. **IN CONFINED SPACES:** ‣ Non-sparking protective boots ‣ Static-free clothing. ‣ Ensure availability of lifeline.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear, colourless liquefied extremely flammable gas with a slight, ether-like odour.

Physical state	Liquified Gas	**Relative density (Water = 1)**	0.99 @ 25C
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available

Continued...

Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (mm2/s)**	Not Available
Initial boiling point and boiling range (°C)	-45.9	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	>1 CCL4= 1	**Explosive properties**	Not Available
Flammability	HIGHLY FLAMMABLE.	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	<15	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	>7	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	1169 @ 25C	**Gas group**	Not Available
Solubility in water	Not Available	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	3.2	**VOC g/L**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	‣ Unstable in the presence of incompatible materials. ‣ Product is considered stable. ‣ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material is not classified as causing respiratory irritation under Regulation (EC) No 1272/2008 (CLP), as amended. Nevertheless, inhalation of the material, particularly following prolonged exposure, may cause respiratory discomfort and, occasionally, respiratory distress. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Continued...

	Common, generalised symptoms associated with non-toxic gas inhalation include : • central nervous system effects such as headache, confusion, dizziness, progressive stupor, coma and seizures; • respiratory system complications may include tachypnoea and dyspnoea; • cardiovascular effects may include circulatory collapse and arrhythmias; • gastrointestinal effects may also be present and may include mucous membrane irritation and nausea and vomiting.
Ingestion	Overexposure is unlikely in this form. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	The material is not classified as a skin irritant under Regulation (EC) No 1272/2008 (CLP), as amended. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not classified as an eye irritant under Regulation (EC) No 1272/2008 (CLP), as amended, direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Direct contact with the eye may not cause irritation because of the extreme volatility of the gas; however concentrated atmospheres may produce irritation after brief exposures..
Chronic	On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Principal route of occupational exposure to the gas is by inhalation. It is generally accepted that the fluorocarbons are less toxic than the corresponding halogenated aliphatic based on chlorine. Repeated inhalation exposure to the fluorocarbon FC-11 does not produce pathologic lesions of the liver and other visceral organs in experimental animals. There has been conjecture in non-scientific publications that fluorocarbons may cause leukemia, cancer, sterility and birth defects; these have not been verified by current research. The high incidence of cancer, spontaneous abortion and congenital anomalies amongst hospital personnel, repeatedly exposed to fluorine-containing general anaesthetics, has caused some scientists to call for a lowering of the fluorocarbon exposure standard to 5 ppm since some are mutagens.

R-454C	**TOXICITY**	**IRRITATION**
	Not Available	Not Available
2,3,3,3-tetrafluoropropene	**TOXICITY**	**IRRITATION**
	Inhalation (Rat) LC50: >86.831 ppm4h[2]	Not Available
difluoromethane	**TOXICITY**	**IRRITATION**
	Inhalation (Rat) LC50: >760000 ppm4h[2]	Not Available
	Oral (Mouse) LD50; 1810 mg/kg[2]	

Legend:	*1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances*

2,3,3,3-TETRAFLUOROPROPENE	Mutagenicity : Did not cause genetic damage in animals. Did not cause genetic damage in cultured mammalian cells. Experiments showed mutagenic effects in cultured bacterial cells. Reproductive toxicity : Animal testing showed no reproductive toxicity. Teratogenicity : Animal testing showed effects on embryo-fetal development at levels equal to or above those causing maternal toxicity. * Vendor For similar product, 1,3,3,3-tetrafluoropropene HFO-1234ze is not likely to accumulate in the bodies of humans or animals HFO-1234ze is practically non-toxic. Short-term exposures at levels higher than 10% have not induced cardiac sensitization to adrenalin nor induced serious toxic effects. Rats and rabbits did not exhibit any serious toxic, developmental or reproductive effects even with exposures to high levels of HFO-1234ze. Based on a series of mutagenicity and genomics studies, the cancer risk for HFO-1234ze is LOW The fluoroalkenes vary widely in acute inhalation toxicity. Those, such as perfluoroisobutylene, PFIB, the most highly toxic member, attacks the pulmonary epithelium of rats eventuating in edema and death after a delay of about one day. Other fluoroalkenes, such as hexafluoropropylene (HFP) or chlorotrifluoroethylene (CTFE), also cause pulmonary injury but at lower concentrations produce concentration dependent changes in the renal concentrating mechanism of the rat. Changes in the CNS of rats and rabbits have also been reported for CTFE. Disinfection by products (DBPs) re formed when disinfectants such as chlorine, chloramine, and ozone react with organic and inorganic matter in water. The observations that some DBPs such as trihalomethanes (THMs), di-/trichloroacetic acids, and 3-chloro-4-(dichloromethyl)-5-hydroxy-2(5H)-furanone (MX) are carcinogenic in animal studies have raised public concern over the possible adverse health effects of DBPs. To date, several hundred DBPs have been identified. Numerous haloalkanes and haloalkenes have been tested for carcinogenic and mutagenic activities. n general, the genotoxic potential is dependent on the nature, number, and position of halogen(s) and the molecular size of the compound.

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✗

Continued...

Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ *– Data either not available or does not fill the criteria for classification*
✓ *– Data available to make classification*

SECTION 12 Ecological information

Toxicity

R-454C

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

2,3,3,3-tetrafluoropropene

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	>2.5mg/l	2
EC50	48h	Crustacea	65mg/l	2
NOEC(ECx)	72h	Algae or other aquatic plants	>=2.5mg/l	2
LC50	96h	Fish	33mg/l	2
ErC50	72h	Algae or other aquatic plants	>100mg/l	2

difluoromethane

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	>114mg/l	2
EC50	48h	Crustacea	>97.9mg/l	2
NOEC(ECx)	96h	Fish	10mg/l	2
EC50	96h	Algae or other aquatic plants	142mg/l	2
LC50	96h	Fish	>81.8mg/l	2

Legend: *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data 8. User defined data*

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2,3,3,3-tetrafluoropropene	HIGH	HIGH
difluoromethane	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
2,3,3,3-tetrafluoropropene	LOW (LogKOW = 2.15)
difluoromethane	LOW (LogKOW = 0.2)

Mobility in soil

Ingredient	Mobility
2,3,3,3-tetrafluoropropene	LOW (Log KOC = 154.4)
difluoromethane	LOW (Log KOC = 23.74)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- Evaporate or incinerate residue at an approved site.
- Return empty containers to supplier.
- Ensure damaged or non-returnable cylinders are gas-free before disposal.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Continued...

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.
DO NOT dispose to a landfill.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2YE

Land transport (UN)

14.1. **UN number or ID number**	3161
14.2. **UN proper shipping name**	LIQUEFIED GAS, FLAMMABLE, N.O.S. (contains difluoromethane and 2,3,3,3-tetrafluoropropene)
14.3. **Transport hazard class(es)**	Class: 2.1 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	Not Applicable
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: 274 Limited quantity: 0

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	3161
14.2. **UN proper shipping name**	Liquefied gas, flammable, n.o.s. * (contains difluoromethane and 2,3,3,3-tetrafluoropropene)
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 2.1 ICAO / IATA Subsidiary Hazard: Not Applicable ERG Code: 10L
14.4. **Packing group**	Not Applicable
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: A1 A807 Cargo Only Packing Instructions: 200 Cargo Only Maximum Qty / Pack: 150 kg Passenger and Cargo Packing Instructions: Forbidden Passenger and Cargo Maximum Qty / Pack: Forbidden Passenger and Cargo Limited Quantity Packing Instructions: Forbidden Passenger and Cargo Limited Maximum Qty / Pack: Forbidden

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	3161
14.2. **UN proper shipping name**	LIQUEFIED GAS, FLAMMABLE, N.O.S. (contains difluoromethane and 2,3,3,3-tetrafluoropropene)
14.3. **Transport hazard class(es)**	IMDG Class: 2.1 IMDG Subsidiary Hazard: Not Applicable

Continued...

14.4. **Packing group**	Not Applicable
14.5 **Environmental hazard**	Not Applicable
14.6 **Special precautions for user**	EMS Number: F-D, S-U Special provisions: 274 Limited Quantities: 0

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2,3,3,3-tetrafluoropropene	Not Applicable
difluoromethane	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
2,3,3,3-tetrafluoropropene	Not Applicable
difluoromethane	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
Not Applicable	Not Applicable

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

2,3,3,3-tetrafluoropropene is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Inventory of Chemicals (NZIoC)

difluoromethane is found on the following regulatory lists

EAEU Ozone-Depleting Substances Subject to Permit/Licensing for Import/Export - List F (Russian)
New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.1A and 2.1.1B	100 kg (or 100 m3 for a permanent gas)	100 kg (or 100 m3 for a permanent gas)

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Continued...

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.1A or 2.1.1B				1 L

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (2,3,3,3-tetrafluoropropene; difluoromethane)
China - IECSC	No (2,3,3,3-tetrafluoropropene; difluoromethane)
Colombia - Colombia National Industrial Chemicals Inventory	No (2,3,3,3-tetrafluoropropene; difluoromethane)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	No (2,3,3,3-tetrafluoropropene)
Vietnam - NCI	Yes
Russia - FBEPH	No (2,3,3,3-tetrafluoropropene)
UAE - Control List (Banned/Restricted Substances)	No (2,3,3,3-tetrafluoropropene; difluoromethane)
Legend:	*Yes = All CAS declared ingredients are on the inventory* *No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.*

SECTION 16 Other information

Revision Date	01/05/2026
Initial Date	26/03/2018

SDS Version Summary

Version	Date of Update	Sections Updated
6.1	15/04/2021	Classification change due to full database hazard calculation/update.
7.1	01/05/2026	Regulatory Update

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard

Continued...

- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.