

OXYGEN COMPRESSED

A-Gas (UK) Ltd

Chemwatch: 1072

Version No: 9.1

Safety data sheet according to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Chemwatch Hazard Alert Code: 2

Initial Date: 04/05/2005

Revision Date: 01/05/2026

Print Date: 25/08/2026

L.REACH.GB.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	OXYGEN COMPRESSED
Synonyms	O2; industrial grade compressed oxygen; food grade compressed oxygen; medical oxygen EP grade; medical dry breathing oxygen; aviators dry breathing oxygen; Gas code 020,024, 025, 027, 224, 226; NZIG Medical Oxygen Code 180; Medical oxygen, compressed;; oxygen, compressed; high purity compressed; medical oxygen; cylinder oxygen
Proper shipping name	OXYGEN, COMPRESSED
Chemical formula	O O2
Other means of identification	Not Available
CAS number	7782-44-7.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Oxygen is used in the manufacture of steel, glass, ethylene oxide, methanol, acrolein, titanium dioxide, vinyl acetate and synthesis gas. In combination with fuel gas such as acetylene, hydrogen or liquefied petroleum gas, it is used in welding, cutting, hardening, scarfing, flame cleaning and heating. Oxygen can be considered for use in any chemical reaction where air is used to give faster reaction time and higher yields. A typical use would be in the treatment of bulk refuse and effluent. In anesthesia, oxygen functions as a carrier gas for the delivery of anesthetic agents to the tissues in the body. In respiratory therapy, oxygen is administered to increase its content and thus decrease the amount of other gases circulating in the blood. Oxygen is also widely used in high altitude and underwater breathing, and in hyperbaric chambers. Other medical applications are in anaesthesia and respiratory therapy.
Uses advised against	No specific uses advised against are identified.

1.3. Details of the manufacturer or importer of the safety data sheet

Manufacturer/Supplier	A-Gas (UK) Ltd
Address	Banyard Road, Portbury West Bristol BS20 7XH United Kingdom
Telephone	+44 (0) 1275 376600
Fax	[+44] (0) 1275 376601
Website	www.agas.com
Email	info.uk@agas.com

1.4. Emergency telephone number

Association / Organisation	A-Gas (UK) Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	+44 (0) 1275 376600	+44 20 3901 3542 (ID#: 1072)
Other emergency telephone number(s)	Not Available	+44 808 164 9592

SECTION 2 Hazards identification

2.1. Classification of the substance or mixture

Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 ^[1]	H270 - Oxidizing Gases Category 1, H280 - Gases Under Pressure (Compressed Gas)
Legend:	1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

2.2. Label elements

Hazard pictogram(s)	 
---------------------	---

Signal word	Danger
-------------	--------

Hazard statement(s)

H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.

Supplementary statement(s)

EUH044	Risk of explosion if heated under confinement.
--------	--

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

P220	Keep away from clothing and other combustible materials.
P244	Keep valves and fittings free from oil and grease.

Precautionary statement(s) Response

P370+P376	In case of fire: Stop leak if safe to do so.
-----------	--

Precautionary statement(s) Storage

P410+P403	Protect from sunlight. Store in a well-ventilated place.
-----------	--

Precautionary statement(s) Disposal

Not Applicable

Material does not contain any CLP Article 18 substances.

2.3. Other hazards

hydrogen	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
----------	---

This substance/mixture does not meet the criteria for classification as Persistent, Bioaccumulative, and Toxic (PBT) in accordance with Annex XIII, Commission Delegated Regulation (EU) 2017/2100, and Commission Regulation (EU) 2018/605.

This substance/mixture does not meet the criteria for classification as very Persistent and very Bioaccumulative (vPvB) in accordance with Annex XIII, Commission Delegated Regulation (EU) 2017/2100, and Commission Regulation (EU) 2018/605.

This substance/mixture does not meet the criteria for classification as Persistent, Mobile and Toxic (PMT) in accordance with Commission Delegated Regulation (EU) 2023/707.

This substance/mixture does not meet the criteria for classification as very Persistent and very Mobile (vPvM) in accordance with Commission Delegated Regulation (EU) 2023/707.

The substance/mixture does not contain components considered to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605, nor is it included in the list established under REACH Article 59(1), at concentrations equal to or greater than 0.1% (w/w).

No further product hazard information.

SECTION 3 Composition / information on ingredients

3.1.Substances

OXYGEN COMPRESSED

1. CAS No 2. EC No 3. Index No 4. REACH No	%[weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	SCL / M-Factor	Nanoform Particle Characteristics
1. 7782-44-7. 2. Not Available 3. Not Available 4. Not Available	>99.5	<u>oxygen</u>	Oxidizing Gases Category 1, Gases Under Pressure (Compressed Gas); H270, H280, EUH044 ^[1]	SCL: Not Available Acute M factor: Not Applicable Chronic M factor: Not Applicable	Not Available
1. 7440-37-1 2. 231-147-0 3. Not Available 4. Not Available	<0.5	<u>argon</u>	Gases Under Pressure (Compressed Gas); H280, EUH044 ^[1]	SCL: Not Available Acute M factor: Not Applicable Chronic M factor: Not Applicable	Not Available
1. 7727-37-9. 2. Not Available 3. Not Available 4. Not Available	< 500ppm^	<u>nitrogen</u>	Gases Under Pressure (Compressed Gas); H280, EUH044 ^[1]	SCL: Not Available Acute M factor: Not Applicable Chronic M factor: Not Applicable	Not Available
1. 1333-74-0 2. 215-605-7 3. 001-001-00-9 4. Not Available	< 500ppm^	<u>hydrogen</u>	Flammable gases, Hazard Category 1, Gases Under Pressure; H220, H280 ^[2]	SCL: Not Available Acute M factor: Not Applicable Chronic M factor: Not Applicable	Not Available
Not Available	< 1ppm^	hydrocarbon as methane	Not Applicable	Not Applicable	Not Available

Legend: 1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties

3.2. Mixtures

See 'Information on ingredients' in section 3.1

SECTION 4 First aid measures

4.1. Description of first aid measures

Eye Contact	▶ If product comes in contact with eyes remove the patient from gas source or contaminated area. ▶ Take the patient to the nearest eye wash, shower or other source of clean water. ▶ Open the eyelid(s) wide to allow the material to evaporate. ▶ Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners. ▶ The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage. ▶ Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) ▶ Transport to hospital or doctor. ▶ Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur. ▶ If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage. ▶ Ensure verbal communication and physical contact with the patient. DO NOT allow the patient to rub the eyes DO NOT allow the patient to tightly shut the eyes DO NOT introduce oil or ointment into the eye(s) without medical advice DO NOT use hot or tepid water.
Skin Contact	If skin contact occurs: ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	▶ Following exposure to gas, remove the patient from the gas source or contaminated area. ▶ NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. ▶ Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. ▶ If the patient is not breathing spontaneously, administer rescue breathing. ▶ If the patient does not have a pulse, administer CPR. ▶ If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. ▶ Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction. ▶ Keep the patient warm, comfortable and at rest while awaiting medical care.

Continued...

OXYGEN COMPRESSED

	▶ MONITOR THE BREATHING AND PULSE, CONTINUOUSLY. ▶ Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	▶ Not considered a normal route of entry.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

5.1. Extinguishing media

FOR SMALL FIRE:

- ▶ USE FLOODING QUANTITIES OF WATER.
- ▶ **DO NOT** use dry chemical, CO₂, foam or halogenated-type extinguishers.

FOR LARGE FIRE

- ▶ Flood fire area with water from a protected position

5.2. Special hazards arising from the substance or mixture

Fire Incompatibility	▶ Avoid storage with reducing agents.
----------------------	---

5.3. Advice for firefighters

Fire Fighting	----- GENERAL ----- ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus and protective gloves. ▶ Fight fire from a safe distance, with adequate cover. ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. ▶ The material may provide sufficient oxygen to make the fire fierce and self sustaining. ▶ Smothering action may not be effective for established fire. ▶ Intense heat may cause spontaneous decomposition (detonation). ▶ Due to possibility of reignition, extinguished residues must be thoroughly cooled before approaching.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	▶ Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. ▶ DO NOT enter confined spaces where gas may have accumulated. ▶ Increase ventilation.
Major Spills	Evacuate area. Eliminate all sources of ignition, NO smoking, No naked lights. ▶ Clear area of all unprotected personnel and move upwind. ▶ Alert Emergency Authority and advise them of the location and nature of hazard. ▶ Wear breathing apparatus and protective gloves. ▶ Prevent by any means available, spillage from entering drains and water-courses. ▶ Remove leaking cylinders to a safe place. ▶ Fit vent pipes. Release pressure under safe, controlled conditions ▶ Burn issuing gas at vent pipes. ▶ DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Continued...

OXYGEN COMPRESSED

Safe handling	Concentrated (i.e. compressed,pure) oxygen turns most materials, including metals, into a fuel. Never use oil or grease on oxygen cylinder valves or regulators. It readily causes an explosion. · Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature · The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines. · Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended. · Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas. ▶ DO NOT transfer gas from one cylinder to another.
Fire and explosion protection	See section 5
Other information	▶ Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. ▶ Such compounds should be sited and built in accordance with statutory requirements. ▶ The storage compound should be kept clear and access restricted to authorised personnel only. ▶ Cylinders stored in the open should be protected against rust and extremes of weather.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	▶ Cylinder: ▶ Ensure the use of equipment rated for cylinder pressure. ▶ Ensure the use of compatible materials of construction. ▶ Valve protection cap to be in place until cylinder is secured, connected. ▶ Cylinder must be properly secured either in use or in storage.
Storage incompatibility	Oxygen: ▶ is a powerful oxidiser ▶ is non-flammable but may initiate fire or explosions, or enhance the combustibility or oxidation rate of materials that were non-combustible in air ▶ at high concentrations (above 24%) will promote or support and accelerate the combustion of combustible and flammable materials ; noncombustible materials such as steel and other metals will burn in pure oxygen. ▶ reacts exothermically with many materials ▶ reacts explosively with phosphine, hydrazine, hydrogen sulfide, ethers, alcohols and hydrocarbons ▶ reacts violently with reducing agents and all easily oxidisable materials; contact may cause fire/ explosion NOTE: the heat of water will vigorously vapourise liquid oxygen. The low temperature may cause brittleness on contact with some materials Keep away from clothing, lubricants, greases, elastic polymers and rubbers. The slightest increase in atmospheric oxygen will amplify the flammability and burning rate of any material including the human body. ▶ Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent. ▶ Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions. ▶ Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous ▶ Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances ▶ Avoid storage with reducing agents.
Hazard categories in accordance with Regulation (EC) No 2012/18/EU (Seveso III)	P4: Oxidising Gases
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	P4 Lower- / Upper-tier requirements: 50 / 200



X — Must not be stored together

O — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

7.3. Specific end use(s)

See section 1.2

SECTION 8 Exposure controls / personal protection

8.1. Control parameters

Continued...

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
Not Available	Not Available	Not Available

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available

Not Applicable

MATERIAL DATA

ppO2 148 mm Hg NA D NA -
Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable.
For oxygen:
No exposure standards available.
NOTE: Detector tubes for oxygen, measuring in excess of 5 vol%, are commercially available

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits.
These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.
CR = Cancer Risk/10000; UF = Uncertainty factor:
TLV believed to be adequate to protect reproductive health:
LOD: Limit of detection
Toxic endpoints have also been identified as:
D = Developmental; R = Reproductive; TC = Transplacental carcinogen
Jankovic J., Drake F.: A Screening Method for Occupational Reproductive
American Industrial Hygiene Association Journal 57: 641-649 (1996)

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
8.2.2. Individual protection measures, such as personal protective equipment	
Eye and face protection	▶ Safety glasses with side shields. ▶ Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	▶ When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection	See Other protection below
Other protection	▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). ▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

Respiratory protection

OXYGEN COMPRESSED

Full face respirator with supplied air.

- ▶ Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- ▶ Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

8.2.3. Environmental exposure controls

See section 12

SECTION 9 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Colourless, odourless, tasteless, neutral gas that supports combustion; slightly soluble in water (0.032 cm ³ /cm ³). Normal air contains 21% oxygen. Permanent gas, critical temperature -118.6 deg. C., critical pressure 5043 KPa. Available in black cylinders fitted with AS2473 Type 10 valve outlet.		
Physical state	Compressed Gas	Relative density (Water = 1)	Not Applicable
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Applicable
Melting point / freezing point (°C)	Not Applicable	Viscosity (mm²/s)	Not Applicable
Initial boiling point and boiling range (°C)	-183	Molecular weight (g/mol)	32.00
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	100
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	1.105	VOC g/L	Not Applicable
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m³)	Not Available	Enclosed Space Ignition Deflagration Density (g/m³)	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10 Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	Extremely high temperatures and pressures. Stable when kept isolated as a compressed gas in cylinders equipped with safety devices to release O ₂ at excessive temperatures and pressures. ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

Continued...

SECTION 11 Toxicological information

11.1. Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	In oxygen-enriched atmospheres both the respiratory and central nervous systems may be affected. No health effects have been observed in humans exposed to concentrations of up to 80 vol% oxygen for a few hours or up to 50 vol% for 24 hours. At pressures above one atmosphere, hyperoxia may appear after 2-6 hours. Symptoms of hyperoxia include cramps, nausea, dizziness, hypothermia, amblyopia (loss of vision), bradycardia, fainting spells and convulsions capable of causing death.
Ingestion	Overexposure is unlikely in this form. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Direct contact with the eye may not cause irritation because of the extreme volatility of the gas; however concentrated atmospheres may produce irritation after brief exposures..
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects. Principal route of occupational exposure to the gas is by inhalation. A variety of central nervous system effects can occur following prolonged exposure to oxygen at partial pressures in excess of 200 kPa: these include dizziness, impaired coordination, visual and hearing disturbances, and seizures. Prolonged exposure at/ or normal elevated pressure may cause severe thickening and scarring of tissue.

OXYGEN COMPRESSED	TOXICITY	IRRITATION
	Not Available	Not Available

Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances
----------------	---

OXYGEN	Inhalation (human) TClO: 100pph (100%)/14hNil reported
ARGON	No known carcinogenic, mutagenic or specific reproductive effects. [BOC]
OXYGEN & ARGON & NITROGEN & HYDROGEN	No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗

Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

11.2.2. Other information

See Section 11.1

SECTION 12 Ecological information

12.1. Toxicity

OXYGEN COMPRESSED	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data				

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
argon	LOW (LogKOW = 0.74)
nitrogen	LOW (LogKOW = 0.67)

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5. Results of PBT and vPvB assessment

	P	B	T	PBT criteria fulfilled?	vP	vB	vPvB criteria fulfilled?
OXYGEN COMPRESSED	No data available	No data available	No data available	No	No data available	No data available	No

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties were found in the current literature.

12.7. Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal	Place leaking oxygen cylinder(s) in a remote place away from combustibles and allow the gas to slowly bleed off to the atmosphere. To increase the rate of controlled evaporation of spilled or leaking oxygen (when desired), spray the spill with large amounts of water. (This may generate a fog and reduce visibility). - Evaporate residue at an approved site. - Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.
------------------------------	---

	▶ Ensure damaged or non-returnable cylinders are gas-free before disposal.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required

	 
Marine Pollutant	NO
HAZCHEM	25

Land transport (ADR-RID)

14.1 UN number or ID number	1072														
14.2 UN proper shipping name	OXYGEN, COMPRESSED														
14.3 Transport hazard class(es)	<table><tr><td>Class</td><td>2.2</td></tr><tr><td>Subsidiary Hazard</td><td>5.1</td></tr></table>	Class	2.2	Subsidiary Hazard	5.1										
Class	2.2														
Subsidiary Hazard	5.1														
14.4. Packing group	Not Applicable														
14.5. Environmental hazard	Not Applicable														
14.6 Special precautions for user	<table><tr><td>Hazard identification (Kemler)</td><td>25</td></tr><tr><td>Classification code</td><td>10</td></tr><tr><td>Hazard Label</td><td>2.2 +5.1</td></tr><tr><td>Special provisions</td><td>355 655 662</td></tr><tr><td>Limited quantity</td><td>0</td></tr><tr><td>Transport Category</td><td>3</td></tr><tr><td>Tunnel Restriction Code</td><td>E</td></tr></table>	Hazard identification (Kemler)	25	Classification code	10	Hazard Label	2.2 +5.1	Special provisions	355 655 662	Limited quantity	0	Transport Category	3	Tunnel Restriction Code	E
Hazard identification (Kemler)	25														
Classification code	10														
Hazard Label	2.2 +5.1														
Special provisions	355 655 662														
Limited quantity	0														
Transport Category	3														
Tunnel Restriction Code	E														

Air transport (ICAO-IATA / DGR)

14.1. UN number	1072														
14.2 UN proper shipping name	Oxygen, compressed														
14.3 Transport hazard class(es)	<table><tr><td>ICAO/IATA Class</td><td>2.2</td></tr><tr><td>ICAO / IATA Subsidiary Hazard</td><td>5.1</td></tr><tr><td>ERG Code</td><td>2X</td></tr></table>	ICAO/IATA Class	2.2	ICAO / IATA Subsidiary Hazard	5.1	ERG Code	2X								
ICAO/IATA Class	2.2														
ICAO / IATA Subsidiary Hazard	5.1														
ERG Code	2X														
14.4. Packing group	Not Applicable														
14.5. Environmental hazard	Not Applicable														
14.6 Special precautions for user	<table><tr><td>Special provisions</td><td>A175 A302</td></tr><tr><td>Cargo Only Packing Instructions</td><td>200</td></tr><tr><td>Cargo Only Maximum Qty / Pack</td><td>150 kg</td></tr><tr><td>Passenger and Cargo Packing Instructions</td><td>200</td></tr><tr><td>Passenger and Cargo Maximum Qty / Pack</td><td>75 kg</td></tr><tr><td>Passenger and Cargo Limited Quantity Packing Instructions</td><td>Forbidden</td></tr><tr><td>Passenger and Cargo Limited Maximum Qty / Pack</td><td>Forbidden</td></tr></table>	Special provisions	A175 A302	Cargo Only Packing Instructions	200	Cargo Only Maximum Qty / Pack	150 kg	Passenger and Cargo Packing Instructions	200	Passenger and Cargo Maximum Qty / Pack	75 kg	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden
Special provisions	A175 A302														
Cargo Only Packing Instructions	200														
Cargo Only Maximum Qty / Pack	150 kg														
Passenger and Cargo Packing Instructions	200														
Passenger and Cargo Maximum Qty / Pack	75 kg														
Passenger and Cargo Limited Quantity Packing Instructions	Forbidden														
Passenger and Cargo Limited Maximum Qty / Pack	Forbidden														

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1072
14.2 UN proper shipping name	OXYGEN, COMPRESSED

14.3 Transport hazard class(es)	IMDG Class	2.2
	IMDG Subsidiary Hazard	5.1
14.4. Packing group	Not Applicable	
14.5 Environmental hazard	Not Applicable	
14.6 Special precautions for user	EMS Number	F-C, S-W
	Special provisions	355
	Limited Quantities	0

Inland waterways transport (ADN)

14.1. UN number	1072	
14.2 UN proper shipping name	OXYGEN, COMPRESSED	
14.3 Transport hazard class(es)	2.2	5.1
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6 Special precautions for user	Classification code	10
	Special provisions	355; 655; 662
	Limited quantity	0
	Equipment required	PP
	Fire cones number	0

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
oxygen	Not Applicable
argon	Not Applicable
nitrogen	Not Applicable
hydrogen	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
oxygen	Not Applicable
argon	Not Applicable
nitrogen	Not Applicable
hydrogen	Not Applicable

SECTION 15 Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

oxygen is found on the following regulatory lists

Great Britain GB mandatory classification and labelling list (GB MCL List)

argon is found on the following regulatory lists

FEI Equine Prohibited Substances List - Banned Substances

FEI Equine Prohibited Substances List (EPSL)

nitrogen is found on the following regulatory lists

Great Britain GB Biocidal Active Substances

hydrogen is found on the following regulatory lists

Great Britain GB mandatory classification and labelling list (GB MCL List)

Additional Regulatory Information

Not Applicable

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category	P4
-----------------	----

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (oxygen; argon; nitrogen; hydrogen)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (oxygen; argon; nitrogen; hydrogen)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (oxygen; argon; nitrogen; hydrogen)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	01/05/2026
Initial Date	04/05/2005

Full text Risk and Hazard codes

H220	Extremely flammable gas.
------	--------------------------

SDS Version Summary

Version	Date of Update	Sections Updated
8.1	20/06/2022	Expiration. Review and Update
9.1	01/05/2026	Regulatory Update

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

- EN 166 Personal eye-protection
- EN 340 Protective clothing
- EN 374 Protective gloves against chemicals and micro-organisms
- EN 13832 Footwear protecting against chemicals

OXYGEN COMPRESSED

EN 133 Respiratory protective devices

Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDNL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Disclaimer: This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.