

A-Gas R22 A-Gas (S.E.A.) Private Limited

Chemwatch: **15-7563** Version No: **8.1** Safety Data Sheet Chemwatch Hazard Alert Code: 1

Issue Date: 24/12/2019 Print Date: 10/12/2021 L.GHS.SGP.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name A-Gas R22						
Chemical Name	nical Name chlorodifluoromethane					
Synonyms	Mixtures of Chlorofluorocarbons; Hydrochlorofluorocarbons; Hydrofluorocarbons; R-22; CHLORODIFLUOROMETHANE; HCFC-22; DYMEL 22					
Proper shipping name	CHLORODIFLUOROMETHANE (REFRIGERANT GAS R 22)					
Chemical formula	Not Applicable					
Other means of identification	Not Available					

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Refrigerant. for industrial use only.

Details of the supplier of the safety data sheet

Registered company name	A-Gas (S.E.A.) Private Limited	Vemac Services Private Limited				
Address	10 Gul Crescent Singapore 629523 Singapore	10 Gul Crescent 629523 Singapore				
Telephone	Telephone 64673990 +6591823010					
Fax	Fax 65 68366521 64697502					
Website	Website www.agas.com www.agas.com					
Email	Not Available	faizil.akbar@agas.com				

Emergency telephone number

Association / Organisation	Chemwatch	Vemac Services Private Limited		
Emergency telephone numbers	+800 2436 2255	64673990		
Other emergency telephone numbers	+61 2 9186 1132	Not Available		

SECTION 2 Hazards identification

Classification of the substance or mixture

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
75-45-6	>99.5	chlorodifluoromethane

SECTION 4 First aid measures

Eye Contact	 If product comes in contact with eyes remove the patient from gas source or contaminated area. Take the patient to the nearest eye wash, shower or other source of clean water. Open the eyelid(s) wide to allow the material to evaporate. Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners. The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage. Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) Transport to hospital or doctor. Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur. If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage. Ensure verbal communication and physical contact with the patient. DO NOT allow the patient to rub the eyes
-------------	--

A-Gas R22

	DO NOT allow the patient to tightly shut the eyes DO NOT introduce oil or ointment into the eye(s) without medical advice DO NOT use hot or tepid water.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. In case of cold burns (frost-bite): Move casualty into warmt before thawing the affected part; if feet are affected carry if possible Bathe the affected area immediately in luke-warm water (not more than 35 deg C) for 10 to 15 minutes, immersing if possible and without rubbing DO NOT apply hot water or radiant heat. Apply a clean, dry, light dressing of "fluffed-up" dry gauze bandage If a limb is involved, raise and support this to reduce swelling If an wult is involved and where intense pain occurs provide pain killers such as paracetomol Transport to hospital, or doctor Subsequent blackening of the exposed tissue indicates potential of necrosis, which may require amputation.
Inhalation	 Following exposure to gas, remove the patient from the gas source or contaminated area. NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. If the patient is not breathing spontaneously, administer rescue breathing. If the patient does not have a pulse, administer CPR. If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction. Keep the patient warm, comfortable and at rest while awaiting medical care. MONITOR THE BREATHING AND PULSE, CONTINUOUSLY. Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
- There is no specific antidote

C: Decontamination

- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)

D: Enhanced elimination:

- There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.
- POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition
- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient
- DO NOT administer sympathomimetic drugs as they may cause ventricular arrhythmias.

For gas exposures:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

ADVANCED TREATMENT

Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- + Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE: Use extinguishing agent suitable for type of surrounding fire. LARGE FIRE: Cool cylinder. DO NOT direct water at source of leak or venting safety devices as icing may occur.

A-Gas R22

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result Advice for firefighters GENERAL Fire Fighting Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus and protective gloves. Fight fire from a safe distance, with adequate cover. Use water delivered as a fine spray to control fire and cool adjacent area. Although not flammable in air at temperatures up to 100 deg. C at atmospheric temperature, mixtures with high concentrations of air at elevated pressure and / or temperature can become combustible in the presence of an ignition source. The material can also become combustible in an oxygen enriched environment (oxygen concentrations greater than in air). Whether air-mixtures or oxygen-mixtures become combustible depends on temperature, pressure and oxygen concentration. Containers may explode when heated - Ruptured cylinders may rocket ▶ Fire exposed containers may vent contents through pressure relief devices. High concentrations of gas may cause asphyxiation without warning. May decompose explosively when heated or involved in fire. Fire/Explosion Hazard Contact with gas may cause burns, severe injury and/ or frostbite. Decomposition may produce toxic fumes of: carbon monoxide (CO) carbon dioxide (CO2) hydrogen chloride phosgene hydrogen fluoride other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used. DO NOT enter confined spaces where gas may have accumulated. Increase ventilation.
Major Spills	 Clear area of all unprotected personnel and move upwind. Alert Emergency Authority and advise them of the location and nature of hazard. Wear breathing apparatus and protective gloves. Prevent by any means available, spillage from entering drains and water-courses. Remove leaking cylinders to a safe place. Fit vent pipes. Release pressure under safe, controlled conditions Burn issuing gas at vent pipes. DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

ecautions for safe handling Safe handling	 Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines. Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended. Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas. DO NOT transfer gas from one cylinder to another. 	
Other information	 Storage temperature: <45 deg.c> Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open. Such compounds should be sited and built in accordance with statutory requirements. The storage compound should be kept clear and access restricted to authorised personnel only. Cylinders stored in the open should be protected against rust and extremes of weather. 	

Conditions for safe storage, including any incompatibilities

Suitable container	 Cylinder: Ensure the use of equipment rated for cylinder pressure. Ensure the use of compatible materials of construction. Valve protection cap to be in place until cylinder is secured, connected. Cylinder must be properly secured either in use or in storage. 					
Storage incompatibility	 Avoid reaction with oxidising agents Haloalkanes: are highly reactive:some of the more lightly substituted lower members are highly flammable; the more highly substituted may be used as fire suppressants, not always with the anticipated results. may react with the lighter divalent metals to produce more reactive compounds analogous to Grignard reagents. 					

may produce explosive compounds following prolonged contact with metallic or other azides



X — Must not be stored together

0 — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Ingredient	Material name		TWA		STEL		Peak	Notes
chlorodifluoromethane	Chlorodifluoromethane		1000 ppm / 3540 mg/m3		Not Available		Not Available	Not Available
TEEL-1		TEEL-2	TEEL-2			TEEL-3		
1,250 ppm		2,400 ppr	n			14,000 ppm		
Original IDLH				Revised IDLH				
Not Available			Not Available					
	chlorodifluoromethane TEEL-1 1,250 ppm Original IDLH	chlorodifluoromethane Chlorodifluoromet TEEL-1 1,250 ppm Original IDLH	chlorodifluoromethane Chlorodifluoromethane TEEL-1 TEEL-2 1,250 ppm 2,400 ppm Original IDLH	chlorodifluoromethane Chlorodifluoromethane 1000 ppm / 35 TEEL-1 TEEL-2 2,400 ppm Original IDLH	Chlorodifluoromethane Chlorodifluoromethane 1000 ppm / 3540 mg/m3 TEEL-1 TEEL-2 1,250 ppm 2,400 ppm Original IDLH Revised IDLH	Chlorodifluoromethane Chlorodifluoromethane 1000 ppm / 3540 mg/m3 Not TEEL-1 TEEL-2 1,250 ppm 2,400 ppm Original IDLH Revised IDLH	Chlorodifluoromethane Chlorodifluoromethane 1000 ppm / 3540 mg/m3 Not Available TEEL-1 TEEL-2 TEEL-3 TEEL-3 1,250 ppm 2,400 ppm 14,000 ppm Original IDLH Revised IDLH Revised IDLH	Chlorodifluoromethane Chlorodifluoromethane 1000 ppm / 3540 mg/m3 Not Available Not Available TEEL-1 TEEL-2 TEEL-3 TEEL-3 1,250 ppm 2,400 ppm 14,000 ppm 14,000 ppm Original IDLH Revised IDLH Revised IDLH Revised IDLH

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.		
Personal protection			
Eye and face protection Chemical goggles. Full face shield may be required for supplementary but never for primary protection of eyes. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, d lenses or restrictions on use, should be created for each workplace or task. Insert of the second sec			
Skin protection	See Hand protection below		
Hands/feet protection Neoprene gloves When handling sealed and suitably insulated cylinders wear cloth or leather gloves. Insulated gloves: NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upon them. Insulated gloves are not made be placed in the liquid; they provide only short-term protection from accidental contact with the liquid. 			
Body protection	See Other protection below		
Other protection Protective overalls, closely fitted at neck and wrist. Eye-wash unit. Ensure availability of lifeline in confined spaces. Staff should be trained in all aspects of rescue work. 			

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear liquefied gas with slight ether-like odour; partly mixes with water.				
Physical state	Liquified Gas	Relative density (Water = 1)	1.19 @ 25 deg.C		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	Neutral	Decomposition temperature	632		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)	-40.8	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	Not Applicable	Taste	Not Available		
Evaporation rate	>1 CCL4 = 1	Explosive properties	Not Available		
Flammability	Not Applicable	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available		
Vapour pressure (kPa)	1044 @ 25 deg.C	Gas group	Not Available		
Solubility in water	Partly miscible	pH as a solution (%)	Not Available		
Vapour density (Air = 1)	3.03 @ 20 deg.C	VOC g/L	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. Presence of elevated temperatures.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Common, generalised symptoms associated with non-toxic gas inhalation include central nervous system effects such as headache, confusion, dizziness, progressive stupor, coma and seizures; respiratory system complications may include tachypnoea and dyspnoea: Inhaled cardiovascular effects may include circulatory collapse and arrhythmias; gastrointestinal effects may also be present and may include mucous membrane irritation and nausea and vomiting Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Exposure to high concentrations of fluorocarbons may produce cardiac arrhythmias or cardiac arrest due sensitisation of the heart to adrenalin or noradrenalin. Deaths associated with exposures to fluorocarbons (specifically halogenated aliphatics) have occurred in occupational settings and in inhalation of bronchodilator drugs. Bronchospasm consistently occurs in human subjects inhaling fluorocarbons. At a measured concentration of 1700 ppm of one of the commercially available aerosols there is a biphasic change in ventilatory capacity, the first reduction occurring within a few minutes and the second delayed up to 30 minutes. Overexposure is unlikely in this form Ingestion Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Skin Contact In common with other halogenated aliphatics, fluorocarbons may cause dermal problems due to a tendency to remove natural oils from the skin causing irritation and the development of dry, sensitive skin. They do not appear to be appreciably absorbed. Material on the skin evaporates rapidly and may cause tingling, chilling and even temporary numbness Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening an stiffening of the skin, a

	progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered). Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening an stiffening of the skin, a progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered).
Chronic	Principal route of occupational exposure to the gas is by inhalation. It is generally accepted that the fluorocarbons are less toxic than the corresponding halogenated aliphatic based on chlorine. Repeated inhalation exposure to the fluorocarbon FC-11 does not produce pathologic lesions of the liver and other visceral organs in experimental animals. There has been conjecture in non-scientific publications that fluorocarbons may cause leukemia, cancer, sterility and birth defects; these have not been verified by current research. The high incidence of cancer, spontaneous abortion and congenital anomalies amongst hospital personnel, repeatedly exposed to fluorine-containing general anaesthetics, has caused some scientists to call for a lowering of the fluorocarbon exposure standard to 5 ppm since some are mutagens. Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

1 C + D22	тохісіту	IRRITATION	
A-Gas R22	Not Available	Not Available	
	ΤΟΧΙCITY	IRRITATION	
chlorodifluoromethane	Inhalation(Rat) LC50; 220000 ppm4h ^[2]	Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

CHLORODIFLUOROMETHANE	and exhalation is the most significant route of elimination f substantial data from exposures to a number of the chlorof CFCs and HCFCs are known to sensitise the heart to adrena CFCs: can be absorbed across the alveolar memb are absorbed rapidly into the blood, follow are absorbed into the blood at a decreasin once in the blood, are absorbed by various	from the body. Controlled studies with vo fluorocarbons. alin-induced arrhythmias. brane, gastro- intestinal tract, or the skin, wing inhalation; ng rate as blood concentration increases; is tissues; is sufficiently long, indicating an equilibri e initial blood level stabilization, and conti rapidly absorbed after inhalation and are or lipid-containing tissues. nts such as chlorine, chloramine, and ozo MS), di-/trichloroacetic acids, and 3-chlor over the possible adverse health effects o for carcinogenic and mutagenic activities. ular size of the compound.	um between the air containing the chlorofluorocarbons nue to enter the body. e distributed by blood into practically all tissues of the ne react with organic and inorganic matter in water. The o-4-(dichloromethyl)-5-hydroxy-2(5H)-furanone (MX) are f DBPs. To date, several hundred DBPs have been
		0	
Acute Toxicity	×	Carcinogenicity	×
Acute Toxicity Skin Irritation/Corrosion	×	Carcinogenicity Reproductivity	× ×
Skin Irritation/Corrosion	×	Reproductivity	×

Legend: 🗙 – Data

 $\pmb{\times}$ – Data either not available or does not fill the criteria for classification $\pmb{\vee}$ – Data available to make classification

SECTION 12 Ecological information

	Endpoint	Test Duration (hr)	Species Value S		Source
A-Gas R22	Not Available	Not Available	Not Available	Not Not Available Availabl	
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50(ECx)	96h	Algae or other aquatic plants	250mg/l	2
chlorodifluoromethane	EC50	48h	Crustacea 433		2
	EC50	96h	Algae or other aquatic plants 250mg/l 2		2
Legend:	-	n 1. IUCLID Toxicity Data 2. Europe ECHA Registered Subs		•	? (QSAR) -
		ty Data (Estimated) 4. US EPA, Ecotox database - Aquatic ion Data 7. METI (Japan) - Bioconcentration Data 8. Venc		ent Data 6. NITE (Japan) -	

Chemwatch: 15-7563	Page 7 of 9	Issue Date: 24/12/2019
Version No: 8.1	A-Gas R22	Print Date: 10/12/2021

On the basis of the available evidence concerning properties and predicted or observed environmental fate and behavior, the material may present a danger to the structure and/ or functioning of the stratospheric ozone layer. DO NOT discharge into sewer or waterways.

Persistence and degradability

5 /		
Ingredient	Persistence: Water/Soil	Persistence: Air
chlorodifluoromethane	LOW	LOW
Bioaccumulative potential		
Ingredient	Bioaccumulation	
chlorodifluoromethane	LOW (LogKOW = 1.08)	
Mobility in soil		
Ingredient	Mobility	

SECTION 13 Disposal considerations

chlorodifluoromethane

Waste treatment methods Product / Packaging disposal Evaporate residue at an approved site. Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase. Ensure damaged or non-returnable cylinders are gas-free before disposal.

SECTION 14 Transport information

Marine Pollutant

Labels Required



LOW (KOC = 23.74)

Land transport (UN)

UN number	1018		
UN proper shipping name	CHLORODIFLUOROMETHANE (REFRIGERANT GAS R 22)		
Transport hazard class(es)	Class2.2SubriskNot Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions Not Applicable Limited quantity 120 ml		

Air transport (ICAO-IATA / DGR)

UN number	1018		
UN proper shipping name	Refrigerant gas R 22; Chlorodifluoromethane		
	ICAO/IATA Class	2.2	
Transport hazard class(es)	ICAO / IATA Subrisk Not Applicable		
	ERG Code 2L		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
	Special provisions		Not Applicable
	Cargo Only Packing Instructions		200
	Cargo Only Maximum Qty / Pack		150 kg
Special precautions for user	Passenger and Cargo Packing Instructions		200
	Passenger and Cargo	Passenger and Cargo Maximum Qty / Pack	
	Passenger and Cargo	Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo	Limited Maximum Qty / Pack	Forbidden

A-Gas R22

UN number	1018	1018		
UN proper shipping name	CHLORODIFLUORON	CHLORODIFLUOROMETHANE (REFRIGERANT GAS R 22)		
Transport hazard class(es)		2.2 Not Applicable		
Packing group	Not Applicable	Not Applicable		
Environmental hazard	Not Applicable			
Special precautions for user	EMS Number Special provisions Limited Quantities			

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

Product name
chlorodifluoromethane
 chlorodifluoromethane

Transport in bulk in accordance with the ICG Code				
	Product name	Ship Type		
	chlorodifluoromethane	Not Available		

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

chlorodifluoromethane is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs Singapore Permissible Exposure Limits of Toxic Substances

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (chlorodifluoromethane)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	24/12/2019
Initial Date	11/06/2008

SDS Version Summary

Version	Date of Update	Sections Updated	
7.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification	
8.1	24/12/2019	Appearance, Use	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks

Chemwatch: 15-7563	Page 9 of 9	Issue Date: 24/12/2019
Version No: 8.1	A-Gas R22	Print Date: 10/12/2021

may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIOC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.