

FLAMMABLE REFRIGERANT MAXIMUM NET RECOVERY WEIGHTS

	Class	Agent	Refillable DOT 4BA / 4BW Cylinders							Refillable DOT 106A/110A		
			Min. Service PSI	30#	50#	100#	125#	240#	500#	1/2 ton	Min. Service PSI	1 ton
HFC	A2L	R32	400	18	31	63	82	160	317	673	800	1123
	A2L	R143a	240	17	31	61	79	155	307	652	500	1088
	A2	R152A	240	17	29	59	77	150	297	630	500	1052
HCFC	A2	R142b	240	23	42	83	108	211	420	889	500	1484
	A2L	R451A	240	20	36	72	94	183	364	770	500	1286
HFO	A2L	R451B	240	20	36	72	94	183	364	771	800	1287
	A2L	R452B	400	18	33	65	85	165	328	696	500	1161
	A2L	R454A	350	19	33	67	87	170	337	715	800	1193
	A2L	R454B	400	18	32	64	84	164	325	689	500	1151
	A2L	R454C	300	19	34	68	89	174	344	730	500	1218
	A2L	R1234yf	240	20	36	71	93	182	361	765	500	1277
	A2L	R1234ze	240	21	38	76	99	194	384	814	500	1359
HC	A3	R290	240	5	9	18	24	47	93	198	500	330
	A3	R600	240	6	11	22	29	56	111	235	500	392
	A3	R600A	240	6	10	21	27	52	104	220	500	368
	A3	R601	240	7	12	24	31	60	119	252	500	420
	A3	R601A	240	7	12	23	30	59	118	249	500	416

This information is believed to be accurate and reliable, but is provided for guidance only. A-Gas accepts no responsibility, and the user assumes all risks and liability for use of this information.