

# A-Gas (South Africa) (Pty) Ltd

Chemwatch: **4151-30** Version No: **7.1** Safety Data Sheet

# Chemwatch Hazard Alert Code: 1

Initial Date: 04/04/2008 Revision Date: 29/04/2021 Print Date: 19/10/2025 L.GHS.ZAF.EN

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

# **Product Identifier**

Product name	1234ZE
Synonyms	C3-H2-F4; CF3CH=CHF; (E)-CF3CH=CHF; (Z)-CF3CH=CHF; 1,3,3,3-tetrafluopropene; 1,3,3,3-tetrafluoropropene, racemic (CAS RN: 1645-83-6); trans-1,3,3,3-tetrafluoropropene [CAS RN: 29118-24-9]; cis-1,3,3,3-tetrafluoropropene [CAS RN: 29118-50-0]; 1,3,3,3-tetrafluoro-1-propene; 1,3,3,3-tetrafluoropropylene; tetrafluorpropene; HFC-1234ze; HCFC-1234ze; HFO-1234ze; R 1234z; R-1234z; R1234z; 1234-ze; Genetron-1234ze; Solstice ze Refrigerant (HFO-1234ze); blowing agent; fluoropropene
Proper shipping name	LIQUEFIED GAS, N.O.S. (contains 1,3,3,3-tetrafluoropropene)
Chemical formula	C3H2F4
Other means of identification	Not Available
CAS number	29118-24-9

# Relevant identified uses of the substance or mixture and uses advised against

Blowing agent for polyurethanes; inert gas for manufacturing Mg alloy.	
Relevant identified uses	The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere
	developing. Before starting consider control of exposure by mechanical ventilation.

# Details of the manufacturer or importer of the safety data sheet

Registered company name	A-Gas (South Africa) (Pty) Ltd
Address	8 Railway Road, Montague Gardens Cape Town 7441 South Africa
Telephone	+27 (0) 21 551 8790
Fax	+27 (0) 21 551 8758
Website	www.agas.com
Email	info.sa@agas.com

# Emergency telephone number

Association / Organisation	A-Gas (South Africa) (Pty) Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	0800 00 5817	0800 296456 (ID#: 4151-30)
Other emergency telephone number(s)	Not Available	+61 3 9573 3188

# **SECTION 2 Hazards identification**

# Classification of the substance or mixture

Classification	Gases Under Pressure (Liquefied Gas)

# **Label elements**

Hazard pictogram(s)



Initial Date: 04/04/2008 Revision Date: 29/04/2021 Print Date: 19/10/2025

Signal word Warning

# Hazard statement(s)

H280 Contains gas under pressure; may explode if heated.

# Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

# Precautionary statement(s) Prevention

Not Applicable

# Precautionary statement(s) Response

Not Applicable

#### Precautionary statement(s) Storage

P410+P403 Protect from sunlight. Store in a well-ventilated place.

# Precautionary statement(s) Disposal

Not Applicable

No further product hazard information.

# **SECTION 3 Composition / information on ingredients**

#### Substances

CAS No	%[weight]	Name
29118-24-9	>99.5	<u>1,3,3,3-tetrafluoropropene</u>

#### Mixtures

See section above for composition of Substances

# **SECTION 4 First aid measures**

# **Description of first aid measures**

Description of first aid measur	
Eye Contact	<ul> <li>If product comes in contact with eyes remove the patient from gas source or contaminated area.</li> <li>Take the patient to the nearest eye wash, shower or other source of clean water.</li> <li>Open the eyelid(s) wide to allow the material to evaporate.</li> <li>Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.</li> <li>The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.</li> <li>Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s)</li> <li>Transport to hospital or doctor.</li> <li>Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.</li> <li>If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.</li> <li>Ensure verbal communication and physical contact with the patient.</li> <li>DO NOT allow the patient to rub the eyes</li> <li>DO NOT allow the patient to tightly shut the eyes</li> <li>DO NOT introduce oil or ointment into the eye(s) without medical advice</li> <li>DO NOT use hot or tepid water.</li> </ul>
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.  In case of cold burns (frost-bite):  Move casualty into warmth before thawing the affected part; if feet are affected carry if possible  Bathe the affected area immediately in luke-warm water (not more than 35 deg C) for 10 to 15 minutes, immersing if possible and without rubbing  DO NOT apply hot water or radiant heat.  Apply a clean, dry, light dressing of "fluffed-up" dry gauze bandage  If a limb is involved, raise and support this to reduce swelling  If an adult is involved and where intense pain occurs provide pain killers such as paracetomol  Transport to hospital, or doctor

• Subsequent blackening of the exposed tissue indicates potential of necrosis, which may require amputation.

Chemwatch: 4151-30 Version No: 7.1 Page **3** of **12** 

Initial Date: **04/04/2008** Revision Date: **29/04/2021** Print Date: **19/10/2025** 

Inhalation	<ul> <li>Following exposure to gas, remove the patient from the gas source or contaminated area.</li> <li>NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer.</li> <li>Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>If the patient is not breathing spontaneously, administer rescue breathing.</li> <li>If the patient does not have a pulse, administer CPR.</li> <li>If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.</li> <li>Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction.</li> <li>Keep the patient warm, comfortable and at rest while awaiting medical care.</li> <li>MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.</li> <li>Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.</li> </ul>
Ingestion	<ul> <li>Not considered a normal route of entry.</li> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
- ▶ There is no specific antidote
- C: Decontamination
- ${}^{\blacktriangleright} \ \ \mbox{Inhalation; remove victim from exposure, and give supplemental oxygen if available.}$
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. **DO NOT** induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)
- D: Enhanced elimination:
  - There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition

- Po not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- ▶ Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient

For frost-bite caused by liquefied petroleum gas:

- If part has not thawed, place in warm water bath (41-46 C) for 15-20 minutes, until the skin turns pink or red.
- Analgesia may be necessary while thawing.
- If there has been a massive exposure, the general body temperature must be depressed, and the patient must be immediately rewarmed by whole-body immersion, in a bath at the above temperature.
- Shock may occur during rewarming.
- Administer tetanus toxoid booster after hospitalization.
- Prophylactic antibiotics may be useful.
- The patient may require anticoagulants and oxygen.

[Shell Australia 22/12/87]

For gas exposures:

BASIC TREATMENT

#### BASIC I REALIVIEIN I

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

-----

# ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

Page 4 of 12 1234ZE

Initial Date: 04/04/2008 Revision Date: 29/04/2021

Print Date: 19/10/2025

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

# **SECTION 5 Firefighting measures**

# **Extinguishing media**

 $\textbf{SMALL FIRE:} \ \textbf{Use extinguishing agent suitable for type of surrounding fire.}$ 

LARGE FIRE: Cool cylinder.

**DO NOT** direct water at source of leak or venting safety devices as icing may occur.

# Special hazards arising from the substrate or mixture

Fire Incompatibility

• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters	
Fire Fighting	GENERAL  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus and protective gloves.  Fight fire from a safe distance, with adequate cover.  Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	According to ASHRAE Standard-2010, R-1234ze(E) is classified in safety group A2L, i.e., it is in the lower segment of the mildly flammable refrigerants. A unique characteristic of this refrigerant is the absence of flammable mixture with air under 30 degree C of ambience. It is non flammable for handling and storage. When utilised in a system, R-1234ze(E) could become flammable with air in case of a leakage. R-1234ze(E) needs 10 times more concentration and 250,000 times more energy than hydrocarbons to become flammable, only above 30 deg C. In case of a flame occurring, the effect of this flame would be extremely mild, as its very low heat of combustion (5 times less than propane) associated to a ultra low burning velocity wouldn't be enough to propagate a fire. When refrigerant classification for industry standards refers to ISO817 or ASHRAE34, it is based on EU definition for PED (or any European directive classification). PED is a European directive and not an industry standard like ISO5149 or EN378. PED has two fluid groups, hazardous and not hazardous. Flammables are in the hazardous group and the PED define flammability according to EU A11 method from European Regulation EC 440/2008. This flammability test. is done at 21 deg C so under EU A11 R-1234ze is not flammable and does not flash (properties correspond to that of PED group 2) Minimum Ignition Energy (54 C, 1 atm): >61000 - <64000 mj.>  • Containers may explode when heated - Ruptured cylinders may rocket  • Fire exposed containers may vent contents through pressure relief devices.  • High concentrations of gas may cause asphyxiation without warning.  • May decompose explosively when heated or involved in fire.  • Contact with gas may cause burns, severe injury and/ or frostbite.  Decomposition may produce toxic fumes of: carbon dioxide (CO2) hydrogen fluoride other pyrolysis products typical of burning organic material.  Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.</li> <li>DO NOT enter confined spaces where gas may have accumulated.</li> <li>Increase ventilation.</li> </ul>
Major Spills	<ul> <li>Clear area of all unprotected personnel and move upwind.</li> <li>Alert Emergency Authority and advise them of the location and nature of hazard.</li> <li>Wear breathing apparatus and protective gloves.</li> <li>Prevent by any means available, spillage from entering drains and water-courses.</li> <li>Remove leaking cylinders to a safe place.</li> <li>Fit vent pipes. Release pressure under safe, controlled conditions</li> <li>Burn issuing gas at vent pipes.</li> <li>DO NOT exert excessive pressure on valve; DO NOTattempt to operate damaged valve.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Initial Date: 04/04/2008 Revision Date: 29/04/2021 Print Date: 19/10/2025

#### **SECTION 7 Handling and storage**

# Precautions for safe handling

- Avoid generation of static electricity. Earth all lines and equipment.
- · Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature

- · The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.
- · Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended.
- · Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas
- ▶ DO NOT transfer gas from one cylinder to another.

# Other information

Safe handling

- Polymerisation may occur slowly at room temperature.
- Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open.
- Such compounds should be sited and built in accordance with statutory requirements.
- The storage compound should be kept clear and access restricted to authorised personnel only.
- Cylinders stored in the open should be protected against rust and extremes of weather.

#### Conditions for safe storage, including any incompatibilities

# Suitable container

- ▶ DO NOT use aluminium or galvanised containers
- Ensure the use of equipment rated for cylinder pressure.
- Ensure the use of compatible materials of construction.
- Valve protection cap to be in place until cylinder is secured, connected.
- Cylinder must be properly secured either in use or in storage.

# Storage incompatibility

As a general rule, hydrofluorocarbons tend to be flammable unless they contain more fluorine atoms than hydrogen atoms.

- Haloalkenes are highly reactive.
- ▶ Some of the more lightly substituted lower members are highly flammable; many members of the group are peroxidisable and polymerisable
- - Avoid reaction or contact with potassium or its alloys although apparently stable on contact with a wide rage of halocarbons, reaction products may be shock-sensitive and may explode with great violence on light impact. Severity generally increases with the degree of halocarbon substitution and potassium-sodium alloys give extremely sensitive mixtures.
  - ▶ Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances















- Must not be stored together
- May be stored together with specific preventions
- May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Not Available

Ingredient	Original IDLH	Revised IDLH
1,3,3,3-tetrafluoropropene	250 mg/m3	Not Available

# MATERIAL DATA

For R-1234 ze(E) OEL TWA: 800 ppm (cf WEEL Occupational Alliance for Risk Science - OARS)

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observableeffect-levels (NOEL) are used to determine these limits where human results are unavailable.

# **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Initial Date: 04/04/2008 Revision Date: 29/04/2021

Print Date: 19/10/2025

	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.	
Individual protection measures, such as personal protective equipment		
Eye and face protection	<ul> <li>Chemical goggles.</li> <li>Full face shield may be required for supplementary but never for primary protection of eyes.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>	
Skin protection	See Hand protection below	
Hands/feet protection	<ul> <li>When handling sealed and suitably insulated cylinders wear cloth or leather gloves.</li> <li>Insulated gloves:</li> <li>NOTE: Insulated gloves should be loose fitting so that may be removed quickly if liquid is spilled upon them. Insulated gloves are not made to permit hands to be placed in the liquid; they provide only short-term protection from accidental contact with the liquid.</li> </ul>	
Body protection	See Other protection below	
Other protection	<ul> <li>Protective overalls, closely fitted at neck and wrist.</li> <li>Eye-wash unit.</li> <li>Ensure availability of lifeline in confined spaces.</li> <li>Staff should be trained in all aspects of rescue work.</li> </ul>	

#### **Respiratory protection**

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

# **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties

Appearance	Liquified gas; does not mix well with water (0.013%). Data for trans-isomer		
Physical state	Liquified Gas	Relative density (Water = 1)	1.098(48 C;1060Kpa)
Odour	Not Available	Partition coefficient n-octanol / water	1.09
Odour threshold	Not Available	Auto-ignition temperature (°C)	368
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	-156	Viscosity (cSt)	199.4 uPa.sec (25 C)
Initial boiling point and boiling range (°C)	-19	Molecular weight (g/mol)	114.04
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	14.4	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	5.6	Volatile Component (%vol)	100
Vapour pressure (kPa)	44 Kpa	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	4.66(25 C; 101 KPa)	VOC g/L	1000
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

Page **7** of **12** 

1234ZE

Initial Date: **04/04/2008** Revision Date: **29/04/2021** 

Print Date: 19/10/2025

**SECTION 10 Stability and reactivity** 

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects

a) Acute Toxicity	sed on available data, the classification criteria are not met.	
b) Skin Irritation/Corrosion	ed on available data, the classification criteria are not met.	
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.	
d) Respiratory or Skin sensitisation	sed on available data, the classification criteria are not met.	
e) Mutagenicity	Based on available data, the classification criteria are not met.	
f) Carcinogenicity	Based on available data, the classification criteria are not met.	
g) Reproductivity	Based on available data, the classification criteria are not met.	
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.	
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.	
j) Aspiration Hazard	Based on available data, the classification criteria are not met.	

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhaled

Exposure to high concentrations of fluorocarbons may produce cardiac arrhythmias or cardiac arrest due sensitisation of the heart to adrenalin or noradrenalin. Deaths associated with exposures to fluorocarbons (specifically halogenated aliphatics) have occurred in occupational settings and in inhalation of bronchodilator drugs.

Bronchospasm consistently occurs in human subjects inhaling fluorocarbons. At a measured concentration of 1700 ppm of one of the commercially available aerosols there is a biphasic change in ventilatory capacity, the first reduction occurring within a few minutes and the second delayed up to 30 minutes.

 $Common, generalised \ symptoms \ associated \ with \ non-toxic \ gas \ inhalation \ include:$ 

- central nervous system effects such as headache, confusion, dizziness, progressive stupor, coma and seizures;
- respiratory system complications may include tachypnoea and dyspnoea;
- $\textcolor{red}{\blacktriangleright} \ \ \text{cardiovascular effects may include circulatory collapse and arrhythmias;}$
- gastrointestinal effects may also be present and may include mucous membrane irritation and nausea and vomiting.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Ingestion

Overexposure is unlikely in this form.

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments

Skin Contact

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Initial Date: 04/04/2008 Revision Date: 29/04/2021

Print Date: 19/10/2025

	In common with other halogenated aliphatics, fluorocarbons may cause dermal problems due to a tendency to remove natural oils from the skin causing irritation and the development of dry, sensitive skin. They do not appear to be appreciably absorbed.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening an stiffening of the skin, a progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered).		
Еуе	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).  Direct contact with the eye may not cause irritation because of the extreme volatility of the gas; however concentrated atmospheres may produce irritation after brief exposures		
Chronic	On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.  Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.  Halogenated oxiranes may arise following epoxidation of haloalkenes.  The metabolism of haloethylenes by microsomal oxidation leading to epoxide formation across the double bond has been proposed. The resulting oxiranes are highly reactive and may covalently bind to nucleic acids leading to mutations and possible cancers A measure of such potential carcinogenicity is the development of significant preneoplastic foci in livers of treated rats.  The carcinogenicity of halogenated oxiranes may lie in the reactivity of an epoxide intermediate.  Principal route of occupational exposure to the gas is by inhalation.  It is generally accepted that the fluorocarbons are less toxic than the corresponding halogenated aliphatic based on chlorine. Repeated inhalation exposure to the fluorocarbon FC-11 does not produce pathologic lesions of the liver and other visceral organs in experimental animals. There has been conjecture in non-scientific publications that fluorocarbons may cause leukemia, cancer, sterility and birth defects; these have not been verified by current research. The high incidence of cancer, spontaneous abortion and congenital anomalies amongst hospital personnel, repeatedly exposed to fluorine-containing general anaesthetics, has caused some scientists to call for a lowering of the fluorocarbon exposure standard to 5 ppm since some are mutagens.		
,	TOXICITY	IRRITATION	
1234ZE	Inhalation (Rat) LC50: >1157.752 ppm4h <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	

	TOXICITY	IRRITATION
1234ZE	Inhalation (Rat) LC50: >1157.752 ppm4h <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute tox	icity 2. Value obtained from manufacturer's SDS. Unless otherwise

specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

# 1,3,3,3 **TETRAFLUOROPROPENE**

Inhalation (rat) NOEL (28 days): >1.5 mg/l \* \* Vendor HFO-1234ze is not likely to accumulate in the bodies of humans or animals HFO-1234ze is practically non-toxic. Short-term exposures at levels higher than 10% have not induced cardiac sensitization to adrenalin nor induced serious toxic effects. Rats and rabbits did not exhibit any serious toxic, developmental or reproductive effects even with exposures to high levels of HFO-1234ze. Based on a series of mutagenicity and genomics studies, the cancer risk for HFO-1234ze is low, no cardiac sensitisation was observed in dogs with exposures up to 120,000 ppm; repeated dose toxicity in rats (13-wk) found mild effects on the heart (NOEL 5,000ppm); in vitro genotoxicity findings include negative Ames Test and negative human lymphocyte chromosome aberration test; in vivo genotoxicity findings in the mouse micronucleus test were negative (inhalation, mammalian bone-marrow cytogenic test with chromosomal analysis).

The fluoroalkenes vary widely in acute inhalation toxicity. Those, such as perfluoroisobutylene, PFIB, the most highly toxic member, attacks the pulmonary epithelium of rats eventuating in edema and death after a delay of about one day. Other fluoroalkenes, such as hexafluoropropylene (HFP) or chlorotrifluoroethylene (CTFE), also cause pulmonary injury but at lower concentrations produce concentration dependent changes in the renal concentrating mechanism of the rat. Changes in the CNS of rats and rabbits have also been reported for CTFE.

Disinfection by products (DBPs) re formed when disinfectants such as chlorine, chloramine, and ozone react with organic and inorganic matter in water. The observations that some DBPs such as trihalomethanes (THMs), di-/trichloroacetic acids, and 3-chloro-4-(dichloromethyl)-5-hydroxy-2(5H)-furanone (MX) are carcinogenic in animal studies have raised public concern over the possible adverse health effects of DBPs. To date, several hundred DBPs have been identified.

Numerous haloalkanes and haloalkenes have been tested for carcinogenic and mutagenic activities. n general, the genotoxic potential is dependent on the nature, number, and position of halogen(s) and the molecular size of the compound.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

🗶 – Data either not available or does not fill the criteria for classification

Data available to make classification

Page 9 of 12 1234ZE

Initial Date: 04/04/2008 Revision Date: 29/04/2021 Print Date: 19/10/2025

#### **SECTION 12 Ecological information**

#### Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>170mg/l	2
	EC50	48h	Crustacea	>160mg/l	2
	EC50(ECx)	48h	Crustacea	>160mg/l	2
1234ZE	LC50	96h	Fish	>117mg/l	2
	ErC50	72h	Algae or other aquatic plants	>170mg/l	2
	EC50	72h	Algae or other aquatic plants	>10mg/l	2
	EC50(ECx)	72h	Algae or other aquatic plants	>10mg/l	2

Bioconcentration Data 8. Vendor Data

GWP 1000 less than SF6 Although practically non-biodegradable, HFO-1234ze is unlikely to impact the aquatic environment because of its high volatility and low toxicity to aquatic organisms. It will migrate almost exclusively into the atmosphere where it will have a lifetime of less than 2 weeks.

Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered. Major Stable Products produced following reaction with ozone. Unsaturated substances (Reactive Emissions) Source of unsaturated substances

In addition to carbon dioxide (CO2), methane (CH4) and nitrous oxide (N2O), the greenhouse gases mentioned in the Kyoto Protocol include synthetic substances that share the common feature of being highly persistent in the atmosphere and exhibiting very high specific radiative forcing (radiative forcing is the change in the balance between radiation coming into the atmosphere and radiation out; a positive radiative forcing tends on average to warm the surface of the earth). These synthetic substances include hydrocarbons that are partially fluorinated (HCFs) or totally fluorinated (PFCs) as well as sulfur hexafluoride (SF6).

The greenhouse potential of these substances, expressed as multiples of that of CO2, are within the range of 140 to 11,700 for HFCs, from 6500 to 9,200 for PFCs and 23,900 for SF6. Once emitted into the atmosphere, these substances have an impact on the environment for decades, centuries, or in certain instances, for thousands of years.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
	No Data available for all ingredients

# Mobility in soil

Ingredient	Aobility	
	No Data available for all ingredients	

# **SECTION 13 Disposal considerations**

# Waste treatment methods

Product / Packaging disposal

- Evaporate residue at an approved site
- Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.
- Ensure damaged or non-returnable cylinders are gas-free before disposal.

# **SECTION 14 Transport information**

#### Labels Required



**Marine Pollutant** 

NO

#### Land transport (UN)

Initial Date: **04/04/2008** Revision Date: **29/04/2021** Print Date: **19/10/2025** 

14.1. UN number or ID number	3163	
14.2. UN proper shipping name	LIQUEFIED GAS, N.O.S. (contains 1,3,3,3-tetrafluoropropene)	
14.3. Transport hazard class(es)	Class Subsidiary Hazard	2.2  Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions  Limited quantity	274; 392 120 ml

# Air transport (ICAO-IATA / DGR)

14.1. UN number	3163			
14.2. UN proper shipping name	Liquefied gas, n.o.s. * (contains 1,3,3,3-tetrafluoropropene)			
14.3. Transport hazard class(es)	ICAO/IATA Class	2.2		
	ICAO / IATA Subsidiary Hazard Not Applicable			
ciass(cs)	ERG Code 2L			
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		200	
	Cargo Only Maximum Qty / Pack		150 kg	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		200	
usei	Passenger and Cargo Maximum Qty / Pack		75 kg	
	Passenger and Cargo Limited Quantity Packing Instructions		Forbidden	
	Passenger and Cargo Limited Maximum Qty / Pack		Forbidden	

# Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3163		
14.2. UN proper shipping name	LIQUEFIED GAS, N.O.S. (contains 1,3,3,3-tetrafluoropropene)		
14.3. Transport hazard class(es)	IMDG Class ———————————————————————————————————	2.2 Not Applicable	
14.4. Packing group	Not Applicable		
14.5 Environmental hazard	Not Applicable		
14.6. Special precautions for user	EMS Number Special provisions Limited Quantities	F-C, S-V 274 392 120 mL	

# 14.7. Maritime transport in bulk according to IMO instruments

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
1,3,3,3-tetrafluoropropene	Not Applicable

# 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type	
1,3,3,3-tetrafluoropropene	Not Applicable	

Page **11** of **12** 

1234ZE

Initial Date: 04/04/2008 Revision Date: 29/04/2021 Print Date: 19/10/2025

# **SECTION 15 Regulatory information**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

# 1,3,3,3-tetrafluoropropene is found on the following regulatory lists

Not Applicable

#### **Additional Regulatory Information**

Not Applicable

#### **National Inventory Status**

Hadional inventory states		
National Inventory	Status	
Australia - AIIC / Australia Non- Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	Yes	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	No (1,3,3,3-tetrafluoropropene)	
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (1,3,3,3-tetrafluoropropene)	
Vietnam - NCI	Yes	
Russia - FBEPH	No (1,3,3,3-tetrafluoropropene)	
UAE - Control List (Banned/Restricted Substances)	No (1,3,3,3-tetrafluoropropene)	
Legend:	Yes = All CAS declared ingredients are on the inventory  No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

#### **SECTION 16 Other information**

Revision Date	29/04/2021
Initial Date	04/04/2008

# **SDS Version Summary**

Version	Date of Update	Sections Updated
6.1	20/07/2017	Toxicological information - Acute Health (skin), Hazards identification - Classification, Disposal considerations - Disposal, Exposure controls / personal protection - Engineering Control, Exposure controls / personal protection - Exposure Standard, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire fighting), Exposure controls / personal protection - Personal Protection (other), Exposure controls / personal protection - Personal Protection (Respirator), Accidental release measures - Spills (major), Accidental release measures - Spills (minor), Handling and storage - Storage (storage requirement), Identification of the substance / mixture and of the company / undertaking - Synonyms, Toxicological information - Toxicity and Irritation (Toxicity Figure), Toxicological information - Toxicity and Irritation (Other), Transport information - Transport, Transport Information
7.1	29/04/2021	Hazards identification - Classification, First Aid measures - First Aid (skin), Exposure controls / personal protection - Personal Protection (eye), Exposure controls / personal protection - Personal Protection (hands/feet)

# Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

# **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit

Chemwatch: **4151-30**Version No: **7.1** 

Page **12** of **12** 

Initial Date: 04/04/2008 Revision Date: 29/04/2021 Print Date: 19/10/2025

- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ► NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

**Disclaimer:** This SDS was prepared by a third party for product identification purposes only and is not endorsed by or affiliated with the original brand owner.